

Tier1
BloombergNEF





M6 HIEFF TWIN MONO

SPxxx-144M

- Standard white (xxx=430~460W)
- Bifacial
- Black frame
- Full black
- Black backsheet
- Panda backsheet

12 Yr quality guarantee | 25 Yr power warranty



WARRANTY & GUARANTEE

Linear output power guarantee
12 years: 91.9% power output
25 years: 84.8% power output



WITHSTAND STRONG

Snow load 5400Pa
Wind load 2400Pa



R&D AND PRODUCTION

Advanced production line.
The leading solar cell cutting process and multi busbar design with SUNPRO Technology.



HIGH EFFICIENCY

Efficiency can reach 21.16%. Excellent low light performance. Higher power output under the conditions of haze, overcast, etc.



POWER TOLERANCE


Power positive tolerance: 0~+3%

Electrical parameters at standard test conditions (STC:AM=1.5, 1000W/m², Cells Temperature 25°C)

Typical type

	430W	435W	440W	445W	450W	455W	460W
Max power(Pmax)	430	435	440	445	450	455	460
Max power voltage(Vmp)	40.60	40.70	40.80	40.90	41.00	41.10	41.20
Max power current(Imp)	10.59	10.69	10.79	10.89	10.98	11.08	11.17
Open circuit voltage(Voc)	49.40	49.50	49.60	49.70	49.80	49.90	50.00
Short circuit current(Isc)	11.11	11.23	11.34	11.45	11.56	11.65	11.69
Module Efficiency(%)	19.78	20.01	20.24	20.47	20.70	20.93	21.16
Max system voltage	DC 1500V(TUV)						
Maximum Series Fuse Rating	20A						

DIMENSIONS AND STRUCTURE



Electrical parameters at NMOT test conditions

(Irradiance 800W/m², Ambient Temperature 20°C, AM 1.5, Wind Speed 1m/s)


Typical type	430W	435W	440W	445W	450W	455W	460W
Max power(Pmax)	349.8	353.9	358.0	362.2	366.0	370.2	374.3
Max power voltage(Vmp)	41.70	41.70	41.80	41.90	42.00	42.10	42.30
Max power current(Imp)	8.40	8.49	8.56	8.64	8.72	8.80	8.85
Open circuit voltage(Voc)	49.60	49.70	49.80	49.90	50.00	50.10	50.20
Short circuit current(Isc)	8.87	8.96	9.05	9.14	9.23	9.30	9.33

Mechanical Data


Dimensions	2094x1038x35mm
Weight	23.5 kg
Glass	3.2mm tempered glass
Output cables	4mm ² , symmetrical lengths 1100mm
Connectors	MC4 compatible IP68
Cell type	Mono-Crystalline PERC, 9BB, 166x83mm
Number of cells	144 cells (Half-Cell)

I-V CHARACTERISTICS AT DIFFERENT IRRADIATION

PV module: SUNPRO, SP460-144M



PV module: SUNPRO, SP460-144M



Temperature Characteristics

Temp.Coeff.of Isc(TK Isc)	0.05%/°C
Temp.Coeff.of Voc(TK Voc)	-0.29%/°C
Temp.Coeff.of Pmax(TK Pmax)	-0.34%/°C
Operating temperature	-40~+85°C
Normal operating cell temperature	44±2°C

Packing Configuration

Container	40'HQ
Pieces per pallet	66
Pallets per container	11
Pieces per container	726

Tests, Certifications and Warranties

Standard tests	IEC 61215, IEC 61730, IEC 61701, IEC 62716, PPP 58042B
System certs	ISO 9001, ISO14001, ISO45001, TUV
Certifications	TUV, AMMONIA AND SALT MIST CORROSION, ANTI-PID, CE, WEEE, INMERTRO, FIRE CERTIFICATE C1
Extreme wind and snow loads testing	Withstand extreme wind(2400 Pascal) and snow loads(5400 Pascal)
Power tolerance	0~+3%
Junction box	IP 68
Warranties	12 years product warranty and 25 years 84.8% of power